

LUNAR with PRODURATEX™ M is manufactured to meet the following typical properties:

Specifications:

Width	54"
Roll Size	30 yds.
Thickness	1.0 mm
Nominal Weight	26 oz. per Lin. yard
Contents	100% Virgin Vinyl
Backing	Q1 Polyester
Cold Crack	-10°F
UV Stabilized Pigments	500 hours minimum
Abrasion Resistance	Heavy Duty Wyzenbeek
Mildew Resistant (ASTM G-21)	Pass
Anti-Bacterial/Anti-Microbial (AATCC 147)	Pass

Suggested Applications:

Automotive, Marine, Office, RV



*This fabric meets or exceeds these ACT performance guidelines. Certification Marks owned by ACT.

Meets Flammability Requirements*:

Motor Vehicle Safety Standard 302
California Technical Bulletin 117-2013, Section 1**
BIFMA, Class A
UFAC, Class 1

*This term and any corresponding data refer to typical performance in the specific test indicated and should not be construed to imply the behavior of this or any other material under actual fire conditions.

** This product, when tested with suitable component materials, may comply with California Technical Bulletin 117-2013, Section 1.

Cleaning Instructions:

This product should be cleaned with mild soap and water. Do not use alcohol based cleaners.

ENDURATEX™ and Produratec™ are trademarks of CGPC America Corp. and may not be used without written permission of CGPC America Corp.



ENDURATEX™
We cover the world.



1181 California Ave, Suite 235, Corona, CA 92881 | 800.243.2472 | 951.332.4100
f: 951.332.4076 | w: enduralex.com | e: cs@enduralex.com
Warehouse Locations: California, Tennessee