



JUNCTION

GENERAL SPECIFICATIONS

| | |
|-------------|-----------------------------------|
| Width | 54" |
| Weight | 26.23 oz / linear yard |
| Composition | 100% Polyester |
| Railroaded | No |
| Repeat | 4.5" H x 2.73" V |
| Finish | Crypton® Stain & Moisture Barrier |

FLAME RETARDANCY SPECIFICATIONS

| | |
|-----------------|--------|
| CAL-TB 117-2013 | Passes |
| NFPA 260 | Passes |
| UFAC Class 1 | Passes |

PERFORMANCE SPECIFICATIONS

| | |
|---------------------------|---------------------------|
| Abrasion | 55,000 DR |
| Colorfastness to Crocking | Wet: 4 Dry: 4.5 |
| Seam Slippage | Fill: 34 Warp: 45.5 |
| Tear Strength | Fill: 77.6 Warp: 129.1 |
| Colorfastness to Light | Class 4 at 40 hours |
| Cleaning Code | WS, BC |
| Brush Pill | Class 4 |
| Bleach Cleanable | Yes |

CLEANING INSTRUCTIONS

Spot clean with upholstery shampoo, foam from a mild detergent, or a mild dry cleaning solvent. Pile fabrics may require brushing to restore appearance. Cushion cover should not be removed and dry cleaned. BC - Lightly spray with a 10% dilution of household bleach and water. After the appropriate contact time, blot surface dry and wipe or rinse with fresh water and blot dry.

REDUCED ENVIRONMENTAL IMPACT

This product does not pose any exposure risks associated with the chemical in Prop 65.

No added flame retardant chemicals

No added anti-bacterial / anti-microbial chemicals

Lead / Heavy metal free

BPA free / Tris free / Formaldehyde free

Does not contain conflict minerals

PFAS Free

*Prop 65 Compliant
*CAB2998 Compliant

RECOMMENDED APPLICATIONS



*ACT® Registered Certification Marks