



BEDFORD

GENERAL SPECIFICATIONS

Width	54"
Weight	15-16 oz/linear yard
Composition	100% Polyester
Backing	SBR
Minimum Yardage	500 Yards
Custom Color	

FLAME RETARDANCY SPECIFICATIONS

CAL-TB 117-2013	Passes
NFPA 260	Passes
UFAC Class 1	Passes

PERFORMANCE SPECIFICATIONS

Abrasion	100,000+ DR
Colorfastness to Crocking	Wet: 5 Dry: 5
Seam Slippage	Fill: 39.8 Warp: 55
Tensile Strength	Fill: 318 Warp: 280
Tear Strength: Tongue Tear	Fill: 62.9 Warp: 59.8
Brush Pill	Class 4.5
Colorfastness to Light	Class 4.5 at 40 Hours
Cleaning Code	SW

CLEANING INSTRUCTIONS

Spot clean with upholstery shampoo, foam from a mild detergent, or mild dry cleaning solvent. Do not saturate with liquid. Pile fabrics may require brushing to restore appearance. Cushion covers should not be removed and dry cleaned.

RECOMMENDED APPLICATIONS



WORKSPACE



HOSPITALITY



RESTAURANT



SENIOR LIVING



*ACT® Registered Certification Marks

FINISHES

