



CLASSIC

GENERAL SPECIFICATIONS

Width	54"
Weight	29 oz/linear yard
Surface Composition	100% PVC
Substrate Composition	100% Polyester
Gauge	0.048
Thickness	1.20 mm

FLAME RETARDANCY SPECIFICATIONS

CAL-TB 117-2013	Passes
NFPA 260	Passes
UFAC Class 1	Passes
FMVSS 302	Passes

REDUCED ENVIRONMENTAL IMPACT

- No added Flame Retardant Chemicals
- No added Anti-Microbial/Anti-Bacterial Chemicals
- Phthalate Free
- Lead/Heavy Metal
- BPA Free/TRIS Free/Formaldehyde Free
- Does not contain Conflict Minerals
- CAB 2998 Compliant

PERFORMANCE SPECIFICATIONS

Abrasion	500,000+ DR
Colorfastness to Crocking	Wet: 5 Dry: 5
Seam Slippage	Fill: 49.6 Warp: 53.3
Tensile Strength	Fill: 102 Warp: 115
Tear Strength: Tongue Tear	Fill: 7.9 Warp: 6.2
Stain Resistant, Anti-Microbial, Mildew Resistant	Passes
Cold Crack	-20°
Colorfastness to Light	1,000 Hours
Bleach Resistant	Yes - 10% Dilution

RECOMMENDED APPLICATIONS



*ACT® Registered Certification Marks

FINISHES

