



# ELIOT

## GENERAL SPECIFICATIONS

Width	54"
Weight	18-19 oz/linear yard
Surface Composition	95% High Solid Polyurethane (Polycarbonate), 5% Silicone
Substrate Composition	100% Polyester
Gauge	0.040
Thickness	1.00 mm

## FLAME RETARDANCY SPECIFICATIONS

CAL-TB 117-2013	Passes
NFPA 260	Passes
UFAC Class 1	Passes

## REDUCED ENVIRONMENTAL IMPACT

This product does not pose any exposure risks associated with the chemicals in Prop 65

Phthalate Free

Lead Free

BPA Free/TRIS Free/Formaldehyde Free

Does not contain Conflict Minerals

Does not contain Flame Retardant Chemicals

Does not contain Anti-Microbial/Anti-Bacterial Chemicals

PVC Free

CAB 2998 Compliant

## PERFORMANCE SPECIFICATIONS

Abrasion	250,000+ DR
Colorfastness to Crocking	Wet: 5 Dry: 5
Seam Slippage	Fill: 62.4 Warp: 62.6
Tensile Strength	Fill: 96 Warp: 118
Tear Strength: Tongue Tear	Fill: 12.1 Warp: 10.4
Colorfastness to Light	200 Hours
Cold Crack	-20°F
Hydrolysis Resistance	15 weeks
Anti-Bacterial	Passes
Anti-Microbial	Passes
Bleach Resistant	Yes — 20% Dilution
Stain Resistant	Yes
Denim Dye Resistant	Yes
Ink Resistant	Yes
Sulfide Stain Resistant	Yes

## RECOMMENDED APPLICATIONS



\*ACT® Registered Certification Marks

## FINISHES

