



PROMISE

GENERAL SPECIFICATIONS

Width	54"
Weight	30 oz/linear yard
Surface Composition	100% PVC
Substrate Composition	100% Polyester
Gauge	0.044-0.48
Thickness	1.1-1.2 mm

FLAME RETARDANCY SPECIFICATIONS

CAL-TB 117-2013	Passes
NFPA 260	Passes
UFAC Class 1	Passes
FMVSS 302	Passes

REDUCED ENVIRONMENTAL IMPACT

No added Flame Retardant Chemicals

No added Anti-Microbial/Anti-Bacterial Chemicals

Phthalate Free

Lead/Heavy Metal

BPA Free/TRIS Free/Formaldehyde Free

Does not contain Conflict Minerals

CAB 2998 Compliant

PERFORMANCE SPECIFICATIONS

Abrasion	350,000 DR
Colorfastness to Crocking	Wet: 5 Dry: 5
Seam Slippage	Fill: 39 Warp: 55
Tensile Strength	Fill: 83 Warp: 98
Tear Strength: Tongue Tear	Fill: 5.2 Warp: 4.9
Stain Resistant, Sulfide Stain Resistant	Passes
Cold Crack	-20°
Colorfastness to Light	650 Hours
Bleach Resistant	Yes - 10% Dilution

RECOMMENDED APPLICATIONS



*ACT® Registered Certification Marks

FINISHES

