



THATCHER

GENERAL SPECIFICATIONS

Width	54"
Weight	23-24 oz/linear yard
Composition	94% Polyester, 4% Polyurethane, 2% Silicone
Backing	Polyurethane
Minimum Yardage Custom Color	500 Yards

FLAME RETARDANCY SPECIFICATIONS

CAL-TB 117-2013	Passes
NFPA 260	Passes
UFAC Class 1	Passes

PERFORMANCE SPECIFICATIONS

Abrasion	100,000+ DR
Colorfastness to Crocking	Wet: 4.5 Dry: 4.5
Seam Slippage	Fill: 80 Warp: 82.5
Tensile Strength	Fill: 80 Warp: 302
Tear Strength: Tongue Tear	Fill: 93.7 Warp: 69.5
Colorfastness to Light	Class 4.5 at 40 Hours
Hydrostatic Pressure (Suter)	270+cm (maximum)
Brush Pill	Class 5

GENERAL TREATMENTS

Moisture Resistant	Yes
Bleach Resistant	Yes – 10% Dilution
Stain Resistant	Yes
Cleaning Code	SW - Spot clean with upholstery shampoo, foam from a mild detergent, or mild dry cleaning solvent.

REDUCED ENVIRONMENTAL IMPACT

This product does not pose any exposure risks associated with the chemicals in Prop 65

No added flame retardant chemicals

No added anti-microbial/anti-bacterial chemicals

PVC free

Phthalate free

RECOMMENDED APPLICATIONS



*ACT® Registered Certification Marks

FINISHES

